



# DRAGON GEAR HD 85W-140

## GEAR OIL

### USES

- Gear boxes, axles, transfer boxes.
- Specially recommended for highly loaded hypoid gears.
- All types of gears when the MIL-L-2105D specification or API GL-5 is required

### PROPERTIES

- High viscosity index.
- High Extreme-Pressure properties..
- Excellent antifoam, anticorrosive and antirust properties.
- Excellent stability in operation

### SPECIFICATIONS

#### International specification

- API GL-5

### CHARACTERISTICS

Test items	Method	Unit	SAE 85W-140
Specific gravity 15/4 °C	ASTM D 1298	-	0.9002
Viscosity 40 °C	ASTM D 445	mm <sup>2</sup> /s	338.4
100 °C		mm <sup>2</sup> /s	25.45
Viscosity index	ASTM D 2270	-	98
Flash point Cleveland	ASTM D 92	°C	238
Pour point	ASTM D 97	°C	-25

Above characteristics are mean values given as an information.

#### S-OIL PHILIPPINES

Lot 3 & 7, Emram Bldg, West Service Road  
Paranaque, Philippines  
1/1

DRAGON GEAR HD 85W140  
2012. 10. 16



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.