



SSU GXO 5W-50

Synthetic technology multigrade oil for Gasoline engines.

USES

- Recommended for all Gasoline engines, specially for most recent technology engines (multi valve, turbocharged, with or without catalytic converter), supercharged or not, in cars.
- Suitable for all journeys (in town, on highways or motorways) and particularly in severe conditions.
- For all driving styles, particularly “vigorous” and high speeds.

PROPERTIES

Very high and constant performance

Excellent engine protection and cleanliness

- Meets API SN requirement, guarantee of an high and constant quality for lubricants.
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high temperature.
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength.

SPECIFICATION

International specifications

- API SN

CHRACTERISTICS

Test Items	Method	Unit	SAE grade 5W-50
Specific Garvity 15/4 °C	ASTM D 1298	-	0.854
Viscosity 40 °C	ASTM D 445	mm ² /s (cSt)	103.0
100 °C		mm ² /s (cSt)	16.6
Viscosity Index	ASTM D 2270	-	175
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-40

Above characteristics are mean values given as an information.

S-OIL TOTAL LUBRICANTS CO., LTD.
 15F, YTN TOWER 6-1 Namdaemmuno 5-ga,
 Jung-gu, Seoul, Korea
 1/1

S-OIL SSU GXO 5W-50
 2012. 06. 08



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
 A material safety data sheet is obtainable via your commercial adviser.